

# CAPPLUS

---

## TECHNOLOGIES

### CS1 Automatic Cotton Inserter



#### SPECIFICATIONS:

COTTON FEED SPEED	60 TO 90/MIN
POWER CONSUMPTION	7.0AMPS
VOLTAGE SUPPLY	110V/60Hz/ 1PH
OPERATING TEMPERATURE	50 TO 104 DEG. F
WORKING AIR PRESSURE	35PSI @ .40CFM
MACHINE WEIGHT	160LBS
MACHINE CRATED WEIGHT	350LBS
MACHINE DIMENSIONS	L25.5" x W24.6" x 55 TO 67"

#### FEATURES INCLUDE:

- RATED AT 60 TO 90 PIECES PER MINUTE
- PRODUCES COTTON LENGTHS FROM 2 TO 9 INCHES IN LENGTH
- INSERTS 1 TO 10 LENGTHS OF COTTON PER BOTTLE
- HOLD DOWN DELAY AT INSERTION STATION
- STAINLESS STEEL CONSTRUCTION
- COUNTS NUMBER OF FILLED BOTTLES
- AUTOMATIC OR MANUAL MODES
- BOTTLE INDEXING
- BOTTLE DETECTION, BOTTLE BACK-UP AND "NO COTTON" SENSORS
- MICROPROCESSOR WITH FLAT PANEL OPERATOR INTERFACE
- ALL STAINLESS STEEL OR DELRIN CONTACT PARTS
- INVERTED "U" SHAPE INSERTION
- 4 TUBE TURRET FOR SMOOTH OPERATION
- LIFT PLATFORM INCLUDED (1" TO 10" BOTTLE HEIGHTS)