

CAPPLUS

TECHNOLOGIES

CVC 100

Top or Side Labeler



CVC 100 SERIES LABELER, TOP OR SIDE PRESSURE SENSITIVE LABELING SYSTEM

FEATURES INCLUDE:

- RATED AT 105' OF LABEL PER MINUTE
- LABELSET SYSTEM AUTO SYSTEM
- DIE CAST LABELING HEADS
- LABEL AND PRODUCT SENSORS
- STAINLESS STEEL CONSTRUCTION
- STEPPER MOTOR DRIVES FOR: LABEL FEED
- MOUNTED ON PORTABLE STAND
- UPGRADABLE FOR FUTURE HOT STAMP INSTALL
- VERTICAL AND HORIZONTAL ADJUSTABILITY
- STEPPER MOTOR DRIVE

SPECIFICATIONS:

LABEL SIZE RANGES:

MAXIMUM LENGTH	1/2" TO 10"
MAXIMUM WIDTH TYPE B	1/2" TO 3/4"

LABEL DISPENSE SPEED	105FT. PER MIN
POWER CONSUMPTION	5.0 AMPS
VOLTAGE TEMPERATURE	115V/60HZ/ 1PH
OPERATING TEMPERATURE	50 TO 104 DEG. F
WORKING AIR PRESSURE	MAX 60 PSI
SERIAL INTERFACE	RS232
WEIGHT	140 LBS
CRATED WEIGHT	340 LBS
DIMENSIONS	L71" x W41" x 59"