

CAPPLUS

TECHNOLOGIES

CVC 300

WRAP AROUND LABELING SYSTEM



CVC 300 SERIES WRAP AROUND PRESSURE SENSITIVE LABELING SYSTEM

FEATURES INCLUDE:

- RATED AT 141' OF LABEL PER MINUTE
- 6' CONVEYOR WITH GUIDE RAILS AND 4" WIDE BELTING
- BOTTLE SEPARATOR
- SELFSET SYSTEM OPERATOR CONTROL SYSTEM
- LCD DISPLAY
- 50 JOB MEMORY
- DIGITAL CONTROLS FOR ALL SPEEDS AND LABELING DATA
- MICROPROCESSOR CONTROLS
- DIE CAST LABELING HEAD
- WRAP STATION
- LABEL AND PRODUCT SENSORS

- STAINLESS STEEL CONSTRUCTION
- STEPPER MOTOR DRIVES FOR: LABEL FEED, WRAP BELT, CONVEYOR
- BOTTLE SEPARATOR

SPECIFICATIONS:

LABEL SIZE RANGES:

MAXIMUM LENGTH	1/2" TO 10"
MAXIMUM WIDTH TYPE C	1/2" TO 6"
LABEL DISPENSE SPEED	141 FT. PER MIN
POWER CONSUMPTION	6.0 AMPS
VOLTAGE TEMPERATURE	115V/60Hz/1PH
OPERATING TEMPERATURE	50 TO 104 DEG. F
WORKING AIR PRESSURE	MAX 60 PSI
SERIAL INTERFACE	RS232
WEIGHT	370 LBS
CRATED WEIGHT	770 LBS
DIMENSIONS	L79" x W41" x 56"