

CAPPLUS

TECHNOLOGIES

CVC 302 HAWK WRAP AROUND LABELING SYSTEM



CVC 302 HAWK WRAP AROUND PRESSURE SENSITIVE LABELING SYSTEM

FEATURES INCLUDE:

- RATED AT 68 METERS OF LABEL PER MINUTE
- 6" TOUCH SCREEN CONTROL DISPLAY WITH VOICE INSTRUCTION
 - SELFSET AUTOMATIC SETUP FOR:
 - LABELING SPEED
 - DISPENSE SPEED
 - LABEL EXTENSION
 - LABEL PLACEMENT
 - SENSITIVITY VALUES
 - 50 JOB SETTINGS
- 9' VARIABLE SPEED CONVEYOR WITH GUIDE RAILS AND 4" WIDE BELTING
- BOTTLE SEPERATOR, AC MOTOR DRIVE, 2 RUBBER METERING WHEELS
- SERVO MOTOR LABELING HEAD
- LABEL AND PRODUCT SENSORS

- SS PANELS, BASE AND FRAME
- ADJUSTABLE CONVEYOR HEIGHT FROM 32.9" TO 33.7 INCHES

SPECIFICATIONS:

LABEL SIZE RANGES:

MAXIMUM LENGTH	1/2" TO 10"
MAXIMUM WIDTH TYPE C	1/2" TO 6"
LABEL DISPENSE SPEED	229FT. PER MIN
LABEL ACCURACY	+/- 0.02 INCHES
POWER CONSUMPTION	6.0 AMPS
VOLTAGE TEMPERATURE	115V/60HZ/1PH
OPERATING TEMPERATURE	50 TO 104 DEG. F
WORKING AIR PRESSURE	MAX 60 PSI
SERIAL INTERFACE	RS232
WEIGHT	370 LBS
CRATED WEIGHT	770 LBS
DIMENSIONS	L79" x W41" x 56"